


SYRIAN PETROLEUM COMPANY

MIDDLE AREA OIL FIELDS

No.

Date.



الشركة السورية للنفط  
مديرية حقول المنطقة الوسطى  
الرقم:  
التاريخ:

**Technical tender book for supplying /800/ ton of BARITE**

- 1-MATERIAL : Drilling grade Barite free flowing powder according OCMA -D F C P 3 & API SPEC.
- 2- Density : 4.2 g/cm<sup>3</sup> Min.
- 3-Residue on 200 mesh: 3 % Max .
- 4- Residue on 325 mesh :15 % Max .
- 5-Alkalinity : 250 mg / l . Max
- 6-Inspection certificate from a neutral company will be required with the shipping documents .
- 7-Technical data sheet from the manufactured company will be required with the technical offer documents .
- 8-Samples : two sealed sample each / 1/ kg the contractor must send it for Middle Area Oil Fields after the contract within 15 days before shipping for testing and if its properties is according T/ B the sample will be the base sample .
- 9-Packing : material must be packed in big bag capacity /1000/ kg or /1500/ kg woven plastic bag with poly-ethylene inner bag with 4 strong hangers .
- 10-Storage : material must be stored under fields conditions in -10 C ° to +50 C °) for 1 year min .
- 11-Representatives of contractor can present on testing of their sampl & shipped material will be tested in Middle Area Fields laboratories .
- 12-The contractor must supply Certificate of Origin & Customs declaration