

I-DRILL PIPE

ITEM	SPECIFICATION	UNIT	QTY
I	New RH drill pipe acc. to API 5 DP and RP7G 2 7/8" OD nominal size, 10.40 lb/ft grade S135, EU , range – 2 with 2 7/8IF ,4 3/8" OD x 1 5/8" ID for pin and box tool joint, friction welded . 18 degree shoulder box conn.	m	6000

Remarks :

- Each pipe should be equipped with pressed steel thread protectors.
- All conn . must be protected by copper or phosphate surface coating.
- All pipe must be protected by external coating for protection from rust.
- All pipe must be marked with A.P.I monogram.
- All certificates of inspection must be enclosed with shipments.
- All pipes ,pressure rating , manufacturing , testing , marking , storage , and shipping to be in accordance with A.P.I specifications.
- API and ISO certificates should be enclosed with the offer.
- Length of the pipes should be (9.30-9.60)M including the upsets and tool joint.
- All pipes must be shipped in bundles and wooden strips are placed to separate each layer.
- Materials shall be unused and of new manufacture only.
- Certificate issued by a neutral international inspection company stating that the materials are conforming with specifications specified in T/B
- Manufacturer and country origin must be mentioned.

- Technical catalog or sheet must enclosed with the offer

- Mechanical test and analysis licenses for metal should be provide with shipment .

- API ~~5DP~~ certificates for drill pipe should be included manufacturer of(pipe , pipe threaded and tool joint) .

- If the bidder has more than one manufacturer the API-5DP (manufacturer of drill pipe assembly ,drill pipe body , tool joint) from Every manufacturer belong to all his items should be submitted .