

(cc)

Hydraulic jar

- Heavy duty design, hydraulic jar. Single acting
- Made from high quality metal
- High performance in the following application : high temp ,high torques , sour medium (H₂S and CO₂)

Specifications as follows :

Item	Tool OD	Top conn box and bottom conn pin	Max BHT(f)	ID	type	Qty
2	9"	7 5/8 REG	300	3	Fishing	4

- - spare parts list for ONE year operation . (about 1000 working hours).

Remarks :

- 1) 2 copy maintenance catalogue should be enclosed with the shipments
- 2) All conn . must be protected by copper or phosphate surface coating. and equipped with metallic thread protect
- 3) All Hydraulic Jar must be protected by external coating for protection from rust..
- 4) All certificates of inspection must be enclosed with shipments.
- 5) Materials shall be unused and of new manufacture only
- 6) the offer should be attached with technical schematic indicates (model, specifications and the main elements of the jar and its P/N , should be mentioned torsion yield lbs(ton) ,tensile yield lbs(ton) ,Approx length extended , Approx Weight , free travel upstroke , free travel down stroke , Pump open area) with the offer
- 7) tensile & torsion yield values should be calculated Acc to API RP 7 G
- 8) Origin country and the manufacturer , should mentioned .
- 9) Threads gauges are manufactured in accordance with API 5 B .
- 10) Valid API 5B certificate should be enclosed with the technical offers